



ACRUX  
Linear Light



# APPLICATION

Schools, Offices, Universities, Malls, Supermarkets, Special design for hotels and palaces.



# FEATURES

Acrux family is used as pure light source, using LED technology. Human and environment friendly, no PB, Hg nor UV which may harm the human and the environment.

Available with different sizes and power rating. Also available with all mounting options (Recessed, staff fitting frame, suspended, surface mounted (Wall, ceiling)).

High power saving fixture, no decay and color temperature shift.

Can be dimmable (through direct control or via network) and not dimmable.



# Acrux Linear Light

## PRODUCT DETAILS

Family Name	Acrux
Part Number	ACR-ALL-15W-XX-SMD-T
Materials	Aluminum, Pc and Eco- Friendly materials, Tempered glass
Installation	Recessed, suspended, surface mounted
Power	15W
Color Rendering Index CRI	80%
Beam Angle	155°
Storage Temperature	- 40 - +85°C
IP Rating	IP20
Lifespan	50,000 Hours
Lumen/Watt	120/130 Lm/W
Input	220 / 50- 60Hz
Power Factor Correction PFC	>.90
LEDs	SMD 2835
Flux	1875 Lum
Correlated Color Temperature CCT	6000/ 4000 / 3000
Warranty	Up to 5 Years


## FEATURES

- ◆ Fixture designed for Harsh and hot environments.
- ◆ High lumen output.
- ◆ Power saving: as it replace the Sodium, metal halide so it save between 50% to 75% of the consumed power.
- ◆ Unlimited numbers of on/off switching cycles.
- ◆ Aluminum heat dissipation module has surface anodic oxidation process to make it very resistant and anti-aging fixture.
- ◆ Over temperature protection, Overload protection, Short-circuit protection, and No-load protection.
- ◆ The Driver is included and it is IP20, and PF>0.9. Dimmable option available with different control options Long life 50000 Hours.
- ◆ Up to five years warranty.



## PRODUCT APPLICATION


Museum, Green House, Factory Industrial area, Football field, Hotel, Warehouse, General Lighting etc...



### PRODUCT DIMENSION

Model	A mm	B mm
ACR-ALL-15W-XX-SMD-T	1000	80

## BEAM ANGLE



Order Code	Color Temperature	LED Power
ACR-ALL-15W-3000-SMD-T	3000K	15W
ACR-ALL-15W-4000-SMD-T	4000K	15W
ACR-ALL-15W-6000-SMD-T	6000K	15W


# Acrux Linear Light

## PRODUCT DETAILS

Family Name	Acrux
Part Number	ACR-ALL-30W-XX-SMD-T
Materials	Aluminum, Pc and Eco- Friendly materials, Tempered glass
Installation	Recessed, suspended, surface mounted
Power	30W
Color Rendering Index CRI	80%
Beam Angle	155°
Storage Temperature	- 40 - +85°C
IP Rating	IP20
Lifespan	50,000 Hours
Lumen/Watt	120/130 Lm/W
Input	220 / 50- 60Hz
Power Factor Correction PFC	>.90
LEDs	SMD 2835
Flux	3750 Lum
Correlated Color Temperature CCT	6000/ 4000 / 3000
Warranty	Up to 5 Years


## FEATURES

- ◆ Fixture designed for Harsh and hot environments.
- ◆ High lumen output.
- ◆ Power saving: as it replace the Sodium, metal halide so it save between 50% to 75% of the consumed power.
- ◆ Unlimited numbers of on/off switching cycles.
- ◆ Aluminum heat dissipation module has surface anodic oxidation process to make it very resistant and anti-aging fixture.
- ◆ Over temperature protection, Overload protection, Short-circuit protection, and No-load protection.
- ◆ The Driver is included and it is IP20, and PF>0.9. Dimmable option available with different control options Long life 50000 Hours.
- ◆ Up to five years warranty.



## PRODUCT APPLICATION


Museum, Green House, Factory Industrial area, Football field, Hotel, Warehouse, General Lighting etc...



### PRODUCT DIMENSION

Model	A mm	B mm
ACR-ALL-30W-XX-SMD-T	1000	80

## BEAM ANGLE



Order Code	Color Temperature	LED Power
ACR-ALL-30W-3000-SMD-T	3000K	30W
ACR-ALL-30W-4000-SMD-T	4000K	30W
ACR-ALL-30W-6000-SMD-T	6000K	30W


# Acrux Linear Light

## PRODUCT DETAILS

Family Name	Acrux
Part Number	ACR-ALL-45W-XX-SMD-T
Materials	Aluminum, Pc and Eco- Friendly materials, Tempered glass
Installation	Recessed, suspended, surface mounted
Power	45W
Color Rendering Index CRI	80%
Beam Angle	155°
Storage Temperature	- 40 - +85°C
IP Rating	IP20
Lifespan	50,000 Hours
Lumen/Watt	120/130 Lm/W
Input	220 / 50- 60Hz
Power Factor Correction PFC	>.90
LEDs	SMD 2835
Flux	5625 Lum
Correlated Color Temperature CCT	6000/ 4000 / 3000
Warranty	Up to 5 Years


## FEATURES

- ◆ Fixture designed for Harsh and hot environments.
- ◆ High lumen output.
- ◆ Power saving: as it replace the Sodium, metal halide so it save between 50% to 75% of the consumed power.
- ◆ Unlimited numbers of on/off switching cycles.
- ◆ Aluminum heat dissipation module has surface anodic oxidation process to make it very resistant and anti-aging fixture.
- ◆ Over temperature protection, Overload protection, Short-circuit protection, and No-load protection.
- ◆ The Driver is included and it is IP20, and PF>0.9. Dimmable option available with different control options Long life 50000 Hours.
- ◆ Up to five years warranty.



## PRODUCT APPLICATION


Museum, Green House, Factory Industrial area, Football field, Hotel, Warehouse, General Lighting etc...



### PRODUCT DIMENSION

Model	A mm	B mm
ACR-ALL-45W-XX-SMD-T	1000	80

## BEAM ANGLE



Order Code	Color Temperature	LED Power
ACR-ALL-45W-3000-SMD-T	3000K	45W
ACR-ALL-45W-4000-SMD-T	4000K	45W
ACR-ALL-45W-6000-SMD-T	6000K	45W



# Acrux HB Linear Light

## PRODUCT DETAILS

Family Name	Acrux
Part Number	ACR-BLL-XW-XXXX
Materials	Powder Coated structure, Polycarbonate Finish
Power Supply	Philips/Gruenes licht/Meanwell/Tridonic
Installation	Suspended, surface mounted
Power	100W/150W/200W
Color Rendering Index CRI	70/80%
Beam Angle	130°
Storage Temperature	- 40 - +85°C
IP Rating	IP66
Lifespan	50,000 Hours
Lumen/Watt	130 Lm/W
Input	220 / 50- 60Hz
Power Factor Correction PFC	>.90
LEDs	Citizen/Philips/Tridonic
Flux	13,000/21,000/28,000 Lum
Correlated Color Temperature CCT	3000 /4000 / 5000K
Warranty	Up to 5 Years

## FEATURES

- ◆ Fixture designed for High Bay Installation.
- ◆ Stylish design with streamlined and visually appealing appearance.
- ◆ Free from streaks and striations, the built in glare control maintains high quality light without compromising comfort.
- ◆ A variety of symmetrical and asymmetrical optics with rectangular and circular patterns.
- ◆ The Driver is included, and PF>0.92. (Dimming as option).
- ◆ 50000 Hours.
- ◆ Up to five years warranty.



3000K  
6000K


80

50 000  
Hours


CRI  
> 80

IP 65

Up to  
5 Year  
Guarantee



## BEAM ANGLE



## PRODUCT APPLICATION

Parking Areas, Factory, Warehouse, Mosque  
General Lighting etc....



PRODUCT DIMENSION		
Model	A mm	B mm
ACR-BLL-100W-XXXX	562	125
ACR-BLL-150W-XXXX	806	125
ACR-BLL-200W-XXXX	1050	125

Order Code	Color Temperature	LED Power
ACR-BLL-100W-XXXX	3000/4000/5000K	100W
ACR-BLL-150W-XXXX	3000/4000/5000K	150W
ACR-BLL-200W-XXXX	3000/4000/5000K	200W


# Acrux HB-G2 Linear Light

## PRODUCT DETAILS

Family Name	Acrux
Part Number	ACR-ALL-XW-XXXX
Materials	PMMA Material
Power Supply	Philips/Gruenes licht/Meanwell/Tridonic
Installation	Suspended, surface mounted
Power	100W/150W/200W
Color Rendering Index CRI	80%
Beam Angle	Asymmetric 30*80°
Storage Temperature	- 40 - +85°C
IP Rating	IP65
Lifespan	50,000 Hours
Lumen/Watt	130 Lm/W
Input	220 / 50- 60Hz
Power Factor Correction PFC	>.90
LEDs	Citizen/Philips/Tridonic
Flux	13,000/21,000/28,000 Lum
Correlated Color Temperature CCT	4000 / 5000K
Warranty	Up to 5 Years


## FEATURES

- ◆ Fixture designed for High Bay Installation.
- ◆ Lens; PMMA material, excellent transparency.
- ◆ Low UGR design, UGR<25.
- ◆ Anti- corrosion, anti-oxidation the heat sink and end cap are powder coating, its could help to resist corrosion and oxidation, and applicable in various environment.
- ◆ Long lifespan driver, the uncovered driver could decrease the affection of heat radiation from the lamp body, which guarantee, the life span of driver.
- ◆ The Driver is included, and PF>0.92. (Dimming as option).
- ◆ Easy to clean up, both end cap of varilinear are friendly hollow-out.
- ◆ 50000 Hours.
- ◆ Up to five years warranty.



## PRODUCT APPLICATION


Parking Areas, Factory, Warehouse, Mosque  
General Lighting etc....



### PRODUCT DIMENSION

Model	A mm	B mm
ACR-ALL-100W-XXXX	580	85.5
ACR-ALL-150W-XXXX	855	85.5
ACR-ALL-200W-XXXX	1130	85.5

## BEAM ANGLE



### Order Code

### Color Temperature

### LED Power

ACR-ALL-100W-XXXX	4000/5000K	100W
ACR-ALL-150W-XXXX	4000/5000K	150W
ACR-ALL-200W-XXXX	4000/5000K	200W

# Acrux WP Linear Light

## PRODUCT DETAILS

Family Name	Acrux
Part Number	ACR-WPL-30W-XX-SMD-T
Materials	Aluminum, Pc and Eco- Friendly materials, Tempered glass
Installation	Recessed, suspended, surface mounted
Power	30W
Color Rendering Index CRI	80%
Beam Angle	155°
Storage Temperature	- 40 - +85°C
IP Rating	IP65
Lifespan	50,000 Hours
Lumen/Watt	120/130 Lm/W
Input	220 / 50- 60Hz
Power Factor Correction PFC	>.90
LEDs	SMD 2835
Flux	3750 Lum
Correlated Color Temperature CCT	6000/ 4000 / 3000
Warranty	Up to 5 Years

## FEATURES

- ◆ Fixture designed for High Bay Installation.
- ◆ Lens; PMMA material, excellent transparency.
- ◆ Low UGR design, UGR<25.
- ◆ Anti- corrosion, anti-oxidation the heat sink and end cap are powder coating, its could help to resist corrosion and oxidation, and applicable in various environment.
- ◆ Long lifespan driver, the uncovered driver could decrease the affection of heat radiation from the lamp body, which guarantee, the life span of driver.
- ◆ The Driver is included, and PF>0.92. (Dimming as option).
- ◆ Easy to clean up, both end cap of varilinear are friendly hollow-out.
- ◆ 50000 Hours.
- ◆ Up to five years warranty.



30w  
3750LM

3000K  
6000K

155


50 000  
Hours

CRI  
> 80


IP 65

RAL  
7045

Up to  
5 Year  
Guarantee



## BEAM ANGLE



## PRODUCT APPLICATION

Museum, Green House, Factory Industrial area, Football field, Hotel, Warehouse, General Lighting etc...



PRODUCT DIMENSION			
Model	A mm	B mm	H mm
ACR-WPL-30W-XX-SMD-T	84	74	1274

Order Code	Color Temperature	LED Power
ACR-WPL-30W-3000-SMD-T	3000K	30W
ACR-WPL-30W-4000-SMD-T	4000K	30W
ACR-WPL-30W-6000-SMD-T	5000K	30W